



ITEM	NAME	REQ	REF	ACCT NO
1	Bolt, stud 3/4"-10x13" w/Sq nuts	4		19-709805
2	Bolt, use at throw rod	1	8007-1	02-054664
3	Bolt, compl., use w/type MJ rods	4	8001-19	01-224201
4	Bolt compl., use w/other vert. sw rods	4	8001-18	
5	Box, junction w/ped. & 36 term.	1		02-070124
6	Bracket, switch adj. W/nut	1		02-081550
7	Conduit, 1-1/2" liquid tight			49-224458
8	Connector, conduit, 1-1/2"	2		49-250804
9	Machine, switch, model 6, 110v. D.C.	1		02-291985
10	Plate, saddle compl.	2	8004-1	02-338612
11	Rod, throw, compl.	1	8002-12	02-458709
12	Rod, throw, compl. use w/lap sw.	1	8002-11	02-439642
13	Bolt grip	4	82163	02-611257
14	Roundal, yellow, 5-3/8" dia.	1		02-467379
15	Roundal, white, 5-3/8" dia.	1		02-467387
16	Roundal, red, 5-3/8" dia.	1		02-469854
17	Signal, type P, with pedestal base	1		02-499133
18	Spike, drive 6 inches long			01-754009
19	Strap, tie - long	1	8014-1	02-556015
20	Strap, tie - short 44-1/2"	2	8014-3	02-556023
21	Unit, light switch corr. indication	1		02-939211
22	Washers, steel spring 3/4" med.	4		19-791209

See notes on sheet 2.

SHEET 1
CONT'D ON SH 2

CONRAIL CS-8030

STANDARD
SWITCH LAYOUT
GRS MODEL 6 SWITCH MACHINE

Approved: *A. Amat* Chief Engineer C&S
D. E. Fisher Chief Engineering Officer

ISSUE DATE: Mar. 21, 1988

REV.		